



## covered in paint

## aspriso limewash interior/exterior

### Intro

Aspriso is the soft matt limewash that gently blooms creating a mottled and aged look with exceptional performance levels. As a new generation limewash, Aspriso instils the classic aesthetic values of limewash with surpassing reliability and durability. Fortified with pure acrylic resin, it embodies exceptional flexibility, adhesion and serviceability to the level of a flat acrylic without the need of a clear sealer. Aspriso is suitable for a broad range of interior and exterior substrates, including primed wood and metal.

### Preparation

Follow the required surface preparation in accordance with standard paint preparation procedures. Apply 1 coat of Covered in Paint's Acrylic Primer Undercoat. Apply Aspriso Limewash by brush with irregular brushstrokes with uniform length. The more natural and free flowing the brushstroke technique, will translate into a more fluid and natural finish. Spread rate is 12-14 m<sup>2</sup> depending on surface porosity and texture. Allow a minimum of 6 hours dry time per coat. Clean up in water.

### Application

- Apply 2 coats by a brush only.
- It is important to 'cut in' progressively and feather the cut in mark into the main body of brushwork.
- Avoid applying the paint too thick, which may cause runs and excessive blooming.
- Place the loaded brush ahead of the wet edge and then work it back onto the main body of painting to prevent doubling up of paint layers.
- A curved wet edge should be maintained. Paint fluidly and steadily across the surface. Do not retouch dry areas.
- Maintain consistent length in the brushstrokes for a unified surface texture pattern - small dabs will look out of place against long sweeping brush strokes. Your natural arm action and brush size should be a guide for the overall brushstroke length.
- On exterior applications walls must be mist sprayed until thoroughly dampened (yet, not glistening with excess water) before application of final coat. If excess water is applied, allow surface to absorb water before applying final coat. Maintain the spray misting procedure ahead of the Limewash application. This procedure is especially important in hotter conditions to reduce the evaporation rate of Limewash and aid the blooming process.
- Walls may be lightly mist sprayed, as soon as final coat is virtually dry (approximately 2-3 hours after painting has been completed depending on drying condition). This procedure can be repeated 5-6 times to aid in the curing of the lime.
- Aspriso Limewash should be applied between the temperature range of 15°C and 28°C. Cooler and more humid conditions create more bloom in the finished look.

### Colours

Aspriso is available in a broad standard and custom colour range.

### Packaging

Aspriso is available in 500ml sample pots (depending on colour), 1litre, 4 litre, 15 litre quantities.

### Contact

For inquiries, please contact Covered in Paint on (02) 9519 0204.