



covered in paint

flat acrylic
interior

Intro

Functional, easy to use and sensitive to the environment, the *Covered in Paint Acrylic* range offers a finish for all interior and exterior elements of a building/home.

Flat Acrylic is a premium flat acrylic finish that delivers a subtle and long lasting finish, dimensional colour and environmental sensitivity with low VOC levels. Ideally suited for interior ceilings and living area, bedroom and lounge room walls that have low traffic.

Location

Flat Acrylic is suitable for interior {and exterior applications, when sheltered from weather}.

Preparation

Ensure surface is in sound condition, clean and dry. Fill cracks or holes with suitable filler. Allow to dry and then sand smooth, prior to applying sealer undercoat. On glossy surfaces remove gloss with 120-220 grade or finer sanding paper. For previously enamelled surfaces test a small area after sanding for adhesion. If necessary oil based undercoat or Sterling Paints Primer Undercoat may be required.

Preparatory coats

New Timber and Masonry surfaces Undercoat with one or two coats of *Covered in Paint Acrylic Primer Undercoat*. Apply two coats of Flat Acrylic. Allow two hours drying between coats, lightly sanding between coats. Brick, Fibre Cement, undercoat with one or two coats of Acrylic Primer Undercoat. Apply two coats of Flat Acrylic. Paper faced plasterboard spot prime joints and any filled areas, apply one or two coats of Primer Undercoat. Then apply two coats Flat Acrylic. Bare Iron, Steel and Galvanised Iron. If the surface is rust-free, apply one or two coats of a Metal Primer. Allow a minimum of 24 hours to dry. Prepare rusted surfaces with appropriate rust treatment prior to painting with metal primer. Allow 24 hours to dry between coats and before applying two coats of Flat Acrylic. New Plaster surfaces apply one coat of pigmented sealer followed by two coats of Flat Acrylic. Previously Painted Surfaces. No undercoat or primer required for surfaces in sound condition - depending on existing colour.

Application

Stir contents thoroughly with a flat stirrer before use. Apply two generous coats by brush, roller or spray equipment. Thining not recommended, if required thin with no more than 5% clean water.

Colours

Available in most standard and custom colours.

Packaging

Available in 1 litre, 4 litre and 15 litre quantities.

Contact

For inquiries, please contact *Covered in Paint* on (02) 9519 0204.

