



Intro

Covered in Paint **Stucco** is a pure essence of stucco that creates a luminous marble finish with a polished lustre. Modelled on the traditional Mediterranean stucco, it features ease of application and exceptional colour luminosity. **Stucco** has been designed with enhanced rheology and work time to create ease of application. Once the final coat has been applied, the surface is worked with a soft cotton rag to achieve a surface lustre that is hard wearing. To reinforce the surface of **Stucco** further and to gain greater luminosity, a wax may be used. Stucco is available in three styles Venetian, Lime based, and Mineral Cement base.

Preparation and Application

On rendered walls sand surface exceptionally well to provide as smooth a surface as possible then apply one coat of primer undercoat sanding surface well once it has dried. Apply one coat of **Stucco** Base to 'set' the wall, sanding surface smooth once dried. To new gyprock, surfaces apply two coats of Covered In Paint primer undercoat after priming joints. To the prepared surface, apply one coat of **Stucco** using a trowel or spatula. Once dried approximately 2-4 hours apply a second coat as before, working the trowel or spatula over the surface as the product dries to create a polished surface. Polish gently with a soft cotton rag as soon as practical after final coat even if surface is not fully dried so long as it is done gently not to disturb finish, and progressively begin to polish harder. Allow 24 hours to dry before final re-polishing with a soft cotton rag.

Colours

Stucco is available in a standard and custom colour range.

Packaging

Stucco is available in 1kg, 6kg and 12kg packaging.

Contact

Inquiries, please contact Covered in Paint on (02) 9519 0204.