



covered in paint

acrylic primer undercoat
interior/exterior

Intro

A water-based, superior quality undercoat that is suitable for interior and exterior use. It is easy to use, dries quickly for same day recoating and provides a smooth even surface for the finishing coat. Suitable for use as an undercoat on fibre cement, timber, hardboard and previously painted surfaces. Can also be used as a sealer basecoat on paper faced plasterboard.

Location

Suitable for use as an undercoat on fibre cement, timber, hardboard and previously painted surfaces. Can also be used as a sealer basecoat on paper faced plasterboard.

Preparation

Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed. Sand the surface smooth and remove all dust. Sand glossy painted surfaces until all gloss is removed. Fill holes and cracks with a suitable stopping compound. Sand lightly to an even finish.

NOTE: Holes and cracks in exterior timber should be filled with a rust durable acrylic putty that is rust durable over nail holes, **after** application of primer then sand and spot prime. For interior timber, use Timber Putty **before** applying the undercoat.

Preparatory coats

Previously Painted Surfaces

Apply one coat of Sterling Paints Acrylic Undercoat to touch-up any bare exterior timber. Allow 2 hours to dry and sand lightly to an even finish. No primer or sealer required on any exposed interior timber. No primer or sealer required on previously painted surfaces in sound condition.

Paper-faced Plasterboard, Fibre Cement, Plaster

Spot prime all joints and any filled areas allow 2 hours to dry and sand lightly to an even finish. Apply two coats of Sterling Paints Acrylic Sealer Undercoat.

Plaster Glass, Fibrous or Hard-Set Plaster

Apply 1 coat of oil based Sealer. Allow 24 hours to dry, followed by 1 coat of Acrylic Primer Undercoat, then sand lightly to an even finish.

Bare Timber

Apply 2 coats of Primer Undercoat allowing 2 hours to dry, sanding lightly to an even finish. Stir the contents thoroughly with a flat stirrer before and during use. Apply 1 or 2 coats by brush, roller or spray equipment. Sand lightly between coats.

Packaging

Available in 1 litre, 4 litre and 15 litre quantities.

Contact

For inquiries, please contact *Covered in Paint* on (02) 9519 0204.

acrylic primer undercoat